

DRIVESHAFT IDENTIFICATION - MEDIUM SERIES

<u>MODEL NO.</u>	<u>SHAFT NO.</u>	<u>ASSY. NO. 1/4</u>	<u>DIA. X LENGTH</u>	<u>NO. TEETH</u>
A	17.31	46.41	5/8 x 24-3/4	14
B	17.32	46.42	5/8 x 24-3/4	14
A74	322	336	11/16 x 25-1/4	17
C	56	90.41	3/4 x 24-7/8	11
EF	57	90.43	3/4 x 24-7/8	11
EFL	200	257	3/4 x 28-5/8	11
J	305	308	5/8 x 24-7/16	14
JL	895	896	5/8 x 29-7/16	14
Q*	349	350	5/8 x 25-1/2	14
QL*	355	358	5/8 x 30-1/2	14
U2,3*	483	484	.669 x 26-9/16	12
U4*	867	868	.669 x 26-9/32	12
U2L	490	491	.669 x 31-9/16	12
U3L*	863	864	.669 x 29-11/16	12
U4L*	881	882	.669 x 29-7/16	12
U4S-4 4 STROKE	1580	1581	.669 x 22-3/4	12
U4L-4 4 STROKE	1584	1585	.669 x 27-3/4	12
Z40/50*	910	911	5/8 x 24-5/8	14
ZL40/50*	914	915	5/8 x 29-7/16	14
AB	987	988	5/8 x 24-1/4	14
ABL	991	992	5/8 x 29-1/4	14
ABL-03	1826	1827	3/4 x 29-9/16	14
AF	1155	1156	3/4 x 24-7/8	14
AFL	1159	1160	3/4 x 29-7/8	14
Z30	1255	1256	5/8 x 24-1/4	14
ZL30	1322	1323	5/8 x 29	14
AF93	1277	1278	3/4 x 24-7/8	17
AH*	1288	1289	.669 x 24	14
AHL*	1345	1346	.669 x 24-1/2	14
AI	1303	1304	.669 x 24-1/2	14
AIL	1360	1361	.669 x 28-5/8	14

*When changing driveshaft length, shift rod length must also be changed

DRIVESHAFT IDENTIFICATION - MEDIUM SERIES

<u>MODEL NO.</u>	<u>SHAFT NO.</u>	<u>ASSY. NO. 1/4</u>	<u>DIA. X LENGTH</u>	<u>NO. TEETH</u>
AJ*	1375	1376	3/4 x 25-1/16	14
AJL*	1435	1436	3/4 x 30-1/16	14
AJL-44 14T 4 STROKE	1444	1445	.707 x 29-3/8	14
AJL-44 16T 4 STROKE	1695	1696	.707 x 29-3/8	16
AJS-43* 4 STROKE	1643	1644	5/8 x 24-9/16	14
AJL-43* 4 STROKE	1647	1648	5/8 x 29-9/16	14
AK*	1399	1400	5/8 x 25-3/4	14
AKL*	1408	1409	5/8 x 30-1/4	14
AKL-44 4 STROKE	1494	1495	3/4 x 30-1/4	14
AK-43* 4 STROKE	1597	1598	5/8 x 30-3/16	14
AKL-43* 4 STROKE	1597	1598	5/8 x 30-3/16	14
AM*	1460	1461	5/8 x 24-3/8	14
AML*	1483	1484	5/8 x 29-3/8	14
BI	2051	2051	5/8 x 24-1/4	14
BIL	2069	2070	5/8 x 29-1/4	14
BB	1897	1898	5/8 x 24-1/2	14
BB LONG	2229	2230	5/8 x 29-1/2	14
BC	1908	1909	5/8 x 26-3/8	14
BCL	2122	2123	5/8 x 31-3/8	14
BD	1926	1927	.669 x 25	10
BL	1695	1696	.707 x 29-3/8	16
BLC	1695	1696	.707 x 29-3/8	16
BT50-4	2200	2201	.669 x 24-3/8	14
BT50L-4	2214	2215	.669 x 29-3/8	14

*When changing driveshaft length, shift rod length must also be changed